

**RATE CONTRACT FOR SUPPLY & INSTALLATION OF  
SECURITY EQUIPMENTS FOR BRANCHES OF  
RAJASTHAN MARUDHARA GRAMIN BANK**

**RAJASTHAN MARUDHARA GRAMIN BANK**



**PRE-QUALIFICATION  
CUM  
TECHNICAL BID**

**Head Office, Tulsi Tower, 9<sup>th</sup> 'B' Road, Sardarpura, Jodhpur ( Raj.)**





## RAJASTHAN MARUDHARAGRAMIN BANK

HEAD OFFICE, TULSI TOWER, 9<sup>th</sup> 'B' ROAD, SARDARPURA, JODHPUR (RAJ.)

RATE CONTRACT FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS FOR BRANCHES IN FIFTEEN DISTRICTS OF RAJASTHAN (JODHPUR, JAIPUR, BIKANER, UDAIPUR, JALORE, SIROHI, JAISALMER, NAGOUR, SRIGANGANAGAR, HANUMANGARH, DAUSA, BARMER, PALI, RAJSAMAND AND PRATAPGARH)

Bank invites sealed tenders from eligible contractors / suppliers for "Supply & installation of SECURITY EQUIPMENTS for branches on rate contract basis. The detailed information, eligibility norms and tender document shall be available during aforesaid period at the Bank's website [www.rmgb.in](http://www.rmgb.in) and [www.tenders.gov.in](http://www.tenders.gov.in). The last date for submission of tender is 31.08.2017 till 15.00 hrs (3.00 PM).

GENERAL MANAGER



## राजस्थान मरुधरा ग्रामीण बैंक

प्रधान कार्यालय, तुलसी टॉवर, 9<sup>th</sup> B रोड, सरदारपुरा, जोधपुर, राजस्थान

बैंक राजस्थान राज्य के 15 जिलो (जोधपुर, जयपुर, बीकानेर, उदयपुर, जैसलमेर, नागौर, दौसा, राजसमन्द, प्रतापगढ, सिरोही, पाली, श्रीगंगानगर, हनुमानगढ, जालोर, बाडमेर) में स्थित शाखाओं में दर संविदा पर सुरक्षा उपकरणों की आपूर्ति और संस्थापन के लिये पात्र ठेकेदारों/आपूर्तिकर्ताओं से सीलबंद निविदा आमंत्रित करता है। विस्तृत सूचना, पात्रता मानदंड और निविदा दस्तावेज इस अवधि में बैंक की वेबसाइट [www.rmgb.in](http://www.rmgb.in) तथा [www.tenders.gov.in](http://www.tenders.gov.in) पर उपलब्ध हैं। निविदा प्रस्तुत किये जाने की समय सीमा 31.08.2017 को अपरान्ह 3.00 बजे तक है।

महाप्रबन्धक





## Rajasthan Marudhara Gramin Bank

Head Office, Tulsi tower, 9<sup>th</sup> 'B' Road, Sardarpura, Jodhpur ( Rajasthan )

Telephone : 0291-2593102 ; Fax: 0291-2657762

### RATE CONTRACT FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS FOR BRANCHES OF RAJASTHAN MARUDHARA GRAMIN BANK

BANK invites sealed tenders i.e. Pre-qualification cum Technical Bids and Price Bid from eligible contractors / suppliers for “SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS FOR ITS BRANCHES SITUATED IN 15 DISTRICTS OF RAJASTHAN ON RATE CONTRACT BASIS.”

The detailed information, eligibility norms and tender document shall also be available during aforesaid period at the Bank's website [www.rmgb.in](http://www.rmgb.in) and [www.tenders.gov.in](http://www.tenders.gov.in)

The last date for submission of tender is 31.08.2017 till 15.00 hrs. The tenders received will be opened on 04.09.2017 at 15.00 hours at the above address in presence of tender committee.

The Bank reserves the right to reject any or all applications without assigning any reason whatsoever.

GENERAL MANAGER





## Rajasthan Marudhara Gramin Bank,

Head Office, Tulsi tower, 9<sup>th</sup> 'B' road, Sardarpura, Jodhpur ( Rajasthan )-342003  
Telephone : 0291-2593102 ; Fax: 0291-2657762

### RATE CONTRACT FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS FOR BRANCHES OF RAJASTHAN MARUDHARA GRAMIN BANK

- PRE-QUALIFICATION CUM TECHNICAL BID
- FINANCIAL BID

1. ISSUE OF TENDERS FROM 16.08.2017 TO 31.08.2017
2. THE DULY COMPLETED 'TECHNICAL BIDS' AND 'FINANCIAL BIDS' (AS PER THE FORMAT) IN SEPARATE SEALED COVER SHOULD BE KEPT IN ONE ENVELOPE SUPERSUBSCRIBED AS 'RATE CONTRACT FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS' SUBMITTED BY 31.08. 2017 UPTO 15.00 HRS (03.00 PM).
3. THE FINANCIAL BIDS SHALL BE OPENED AFTER SCRUTINY OF TECHNICAL BIDS IF FOUND IN ORDER AS PER THE QUALIFYING CRITERIA OF MINIMUM REQUIREMENTS AS MENTIONED AND RELEVANT BIS CERTIFICATIONS.
4. ON SCRUTINY OF TECHNICAL DETAILS IF OFFERED EQUIPMENTS ARE FOUND INELIGIBLE, THE FINANCIAL BID OF THE CONCERNED BIDDER SHALL NOT BE OPENED.
5. LAST DATE OF SUBMISSION 31.08. 2017 UPTO 15.00 HOURS.
6. DATE OF OPENING OF TECHNICAL BID 04.09.2017 BY 15.00 HOURS.
7. FINANCIAL BIDS SHALL BE OPENED AFTER THE SCRUTINY OF TECHNICAL BIDS.
8. PLACE OF SUBMISSION - 'TENDER BOX' AT 3<sup>rd</sup> FLOOR  
RAJASTHAN MARUDHARA GRAMIN BANK  
Tulsi Tower, 9<sup>th</sup> 'B' Road Sardarpura, Jodhpur-342003  
Telephone:0291-2593102 Fax-2657762

CONTACT PERSON : SHRI M.S. CHAMPAWAT

TELEPHONE : 0291-2593102

TENDER Submitted by: M/S. \_\_\_\_\_



## Annexure - I

### **PRE - QUALIFICATION CUM TENDER NOTICE**

#### **RATE CONTRACT FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENTS FOR BRANCHES OF RAJASTHAN MARUDHARA GRAMIN BANK**

Sealed item rate tenders are invited by : RAJASTHAN MARUDHARA GRAMIN BANK  
Head Office, 9<sup>th</sup> 'B' Road, Sardarpura, Jodhpur ( Raj.) -342003  
Telephone: 0291-2593102 Fax-0291-2657762

1. The tender is invited on rate contract basis and the supply will be made upto 31<sup>st</sup> March 2019 as per requirement of the Bank and the same can be extended for another one year with mutual consent of Bank and supplier.
2. The subject tender is submission of bid for pre-qualification cum technical bid. The committee formed by the Bank will evaluate the offer submitted which may include visit to the manufacturing facility also. The Committee will look into various parameters and thereafter pre-qualify eligible agencies who are fulfilling eligibility criteria mentioned in the tender shall be eligible for opening of commercial bid. The approval of contract would be the L1 price offered for individual product. Thus it is likely that there will be more than one agency getting selected for supplying the item in which they have quoted L-1 price. Though bank has right to reject any bid without providing the reason.
3. Tenders will be received upto 15.00 hours on 31.08 2017.
4. No tender will be accepted after the expiry of the time notified for receiving tenders under any circumstances whatsoever.
5. The tender will be opened at 15.00 hours on 04.09.2017 at above address in the presence of authorized representative of Vendors.
6. The Bank reserves the right to reject any or all tenders received without assigning any reasons thereof .
7. The tender rate against each item of work / price indicated in the schedule of quantities and rates / price should be indicated both in words and figures. In case of any discrepancy, the rates indicated in words would prevail.
8. The rates quoted against each item should be including supply, placement , taxes and duty, charges etc. Any statutory change in the tax structure after opening of the tender shall be reimbursed by the Bank as per the prevalent rates. The rates quoted should be inclusive of transportation and delivery charges upto destination of branch/office.
9. Each tender shall be accompanied by Earnest Money deposit of ₹ 2,00,000/- ( Rupees Two lacs only) in the form of fixed deposit /Bank Guarantee in favour of Rajasthan Marudhara Gramin Bank, Jodhpur for a period of 24 months. Tenders without Earnest Money shall be summarily rejected.



10. The Earnest Money deposited shall be returned to the unsuccessful tenderers. Earnest Money submitted by the successful tenderer will be retained by the Bank till completion of the contract period.

11. Bank Guarantee submitted by vendor may be invoked by the Bank / Earnest Money in other forms will be forfeited if Vendor fails to make the delivery in schedule time or breach of terms & conditions of tender / contract.

12. Bidder should sealed and signed the copy of tender document in token of acceptance of terms and conditions of Tender Document.

13. Bank reserves the right to split the work order among L-1, L-2 and L-3 bidders, if L-1 Vendor express its inability in writing to execute the work order and delivery of items in time. In such case, subject to concurrence of L-2 and L-3 bidders to agree to supply the equipments at L-1 price Bank may place the order to L-2 vendor or L-3 vendor in the sequence of their ranking in commercial bid.

14. The tenders in which any of the prescribed conditions are not fulfilled or incomplete in any respect are liable to be rejected.

15. This tender notice shall form part of the contract documents.

**General Manager**



## BIO – DATA OF TENDERER

1. Name of the firm :

Corporate Office Address

Telephone No.

Office  
Residence  
Mobile  
Fax  
E-Mail

Branch Office address

Telephone No.

Office  
Residence  
Mobile  
Fax  
E-Mail

2. a) Whether proprietary/partnership/ :  
Pvt. Ltd. / Public Ltd. (certificate  
of registration / partnership deed  
to be enclosed as Annexure-I).

b) Name of the Proprietor,  
Partners, Directors  
I)  
II)

c) Year of establishment

3. Registration with Tax Authorities

i) Income-tax (PAN) No

ii) GSTIN No.

(copies of certificates of registration with relevant authorities to be enclosed )

4. Furnish copies of audited balance- : Enclosed / Not enclosed  
Sheet and Profit & Loss A/C. for  
the last 5 years i.e. 2012-13, 13-14, 14-15, 15-16, 16-17

5. Details of Blacklisting /Delisting /De-empanelment in last 5 Years.

6. Name & relation, if any, with the staff member of Rajasthan Marudhara Gramin bank.



7. Details of empanelment with Public Sector Banks in India. Provide Empanelment letter of 12 PSU Banks including SBI & its Sponsored RRBs.

8. Turnover in last 5 years:

Sr. No	Year	Turnover ( ₹ in lacs)	Profit / Loss ( ₹ in lacs )
1.	2012-13		
2.	2013-14		
3.	2014-15		
4.	2015-16		
5.	2016-17		

Copies of Audited Balance sheet and P&L Statement for each year to be enclosed.

9. Applicant must furnish a valid Bank Solvency Certificate of value at least ₹ 1.00 crore.

### **DECLARATION**

I / We have read the instructions appended to the proforma and I / We understand that if any false information is detected at a later date, any future contract made between ourselves and Rajasthan Marudhara Gramin Bank, on the basis of the information given by me / us can be treated as invalid by the Bank and I / We will be solely responsible for the consequences.

I / We agree that the decision of Rajasthan Marudhara Gramin Bank in selection of contractors will be final and binding to me / us.

All the information furnished by me / us hereunder is correct to the best of my / our knowledge and belief.

I / We agree that I / we have no objection if enquiries are made about the work listed by me / us in the accompanying sheets.

I / We agree that I / We have not applied in the name of sister concern for the subject empanelment process.

Place :

Date :



SIGNATURE  
NAME & DESIGNATION  
SEAL OF ORGANISATION



## Scope of Work

During the current financial year, the Bank is planning to open about 60 new branches spread in 15 districts of Rajasthan. At least 10% of the branches will be opened with provision of Strong Rooms (Vaults). The Bank has initiated steps to streamline the procurement system of SECURITY EQUIPMENTS, i.e., Cash / Gold Safes, Vault Doors, Fire Resisting Filing Cabinets (FRFC), Fire Resisting Record Cabinet (FRRC) and Safe Deposit Locker Cabinets. Upon approval of price bid, work order will be placed with the selected agencies with a communication to the Bank's Regional Offices. The Head Office will directly place the order of requirement to selected agency to deliver the material at particular branch / office. The selected agency will ensure and deliver the material within 4 to 6 weeks upon such request. The bills are to be submitted directly to Head Office for settlement of dues.

If delays are observed in deliveries late delivery (LD) charges @ 1% per week or part thereof, will be levied for delayed period, maximum upto the ceiling of 10% of purchase order. In case of delay in delivery of goods, Bank reserves the right to cancel the order (partial / whole) given to L-1 vendor and give order to L-2 vendor for getting the work done. In case of delay in delivery, Bank reserves the right to invoke the Bank Guarantee submitted by the vendor or take suitable action as deemed suitable.

\*\*\*\*\*



## Basic Eligibility Criteria

Sr. No	Parameters	Requirements
a.	Average Turnover volume	The company should have Annual Sales turnover of <b>₹ 60.00 Crore or above in Torch &amp; Tool Resistant (TRTL) products</b> in last 5 years, i.e. from year 2012-13 to 2016-17. Audited Balance sheets & Profit & Loss Statements of last 5 years to be submitted.
b.	Profit in the previous financial years	The company should not have incurred loss in the last 5 years, i.e. from year 2012-13 to 2016-17.
c.	Registered Companies	The company should have been registered under the Companies Act at least 10 years earlier from the date of tender opening.
d.	OEMs	The company should be the Original Equipment Manufacturers of Safes, Vault Doors, Locker Units and Fire Resistant Filing Cabinets FRFC and Fire resistant Record Cabinet ) to qualify for the empanelment for the respective products.
e.	In-house manufacturing process	Manufacturing process for Safes, Vault Doors, Locker Units, Fire Resistant Filing Cabinets (FRFC), Fire resistant Record Cabinet and making their locks & keys should be done in-house by the company to qualify for the empanelment for the respective products.
f.	BIS License	The company should have valid BIS licenses ( issued on or before the tender opening date i.e., 04.09.2017 ) for a. Safes b. Vault Doors c. Locker Units d. Fire Resistant Filing Cabinets. e. Fire Resistant Record Cabinet  The list of OEMs posted/updated on the BIS website as on the date of opening of tender process, i.e, 04.09.2017 will be taken as the conclusive proof for the purpose of eligibility.
g.	Network of offices/dealers	The company should have at least 5 dealers in the area where the Bank is operative. Authorised dealer at HO location is must to coordinate and provide services. Provide list of Authorised dealers with contact details and current dealership certificate . Also provide purchase Bill and Sales Bill for 2016-17 to be enclosed.
h.	Empanelment with other PSU	The company should have been in the panel of approved suppliers for Safes, Strong Room doors, Locker Units and FRFCs with the Head Offices of at least 12 public sector banks including SBI and its Sponsored RRBs for the last 5 years and in the current approved panel too.



i.	Random Testing Clause	Applicant must agree to random testing of their products supplied to the Bank at their own cost at the current “Test House” approved by BIS. During Testing, if the quality of these equipments is found unsatisfactory, Bank will blacklist those manufacturers from further empanelment and may inform to IBA accordingly. All costs of Testing including transportation and other expenses shall be borne by the manufacturer. An undertaking to this effect should be submitted along with application.
j.	Blacklisting /Delisting	OEM must not have been blacklisted / Delisted / De-empanelled / De-barred for any product from supplying by any scheduled commercial Bank in the last 5 years and nor shall its name be figured in IBA caution list. A written undertaking has to be given by the OEM in this regard .



### Specific Eligibility Criteria for Vault Door

Sr. No.	Parameters	Requirements	Compliance Yes / No
a.	License	Product to be manufactured as per IS : 11188	
b.	Minimum period of Vault Door manufacturing business	Minimum 10 years	
c.	Vault Doors Manufacturing Capacity	The company should have manufactured not less than 100 TRTL Vault Doors in the past three years, i.e. from the year 2014-15 to 2016-17. Copies of the form 3CA & form 3CD giving quantitative details of TRTL vault doors manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document	
d.	Order execution	Tenderer should have received and supplied atleast one single order of 10 Qty from any PSU Bank / RRB.	

### Specific Eligibility Criteria for Cash Safe

Sr. No	Parameters	Requirements	Compliance Yes / No
a.	License	Product to be manufactured as per IS : 550	
b.	No. of years required in Safe manufacturing Business	Minimum 10 years	
c.	Safe Manufacturing Capacity	The company should have manufactured not less than 1000 Safes in the past three years, i.e. from the year 2014-15 to 2016-17. Copies of the form 3CA & form 3CD giving quantitative details of Safes manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document.	
d.	Order Execution	Tenderer should have received and supplied atleast one single order of 10 Qty from any PSU Bank/ RRB.	



**Specific Eligibility Criteria for Fire Resisting Record Cabinet (FRRC)**

<b>Sr. No.</b>	<b>Parameters</b>	<b>Requirements</b>	<b>Compliance Yes / No</b>
a.	License	Product to be manufactured as per IS : 14203:1999 or UL72 Class 350 for 2 Hr Rating	
b.	No. of years required in FRRC manufacturing Business	Minimum 10 years	
c.	FRRC Manufacturing Capacity	The company should have manufactured not less than 1000 FRRCs in the past three years, i.e. from the year 2014-15 to 201617. Copies of the form 3CA & form 3CD giving quantitative details of FRRCs manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document.	
d.	Order Execution	Tenderer should have received and supplied at least one single order of 10 Qty from any PSU Bank/ RRB.	

**Specific Eligibility Criteria for Fire Resistance Filling Cabinet (FRFC)**

<b>Sr. No.</b>	<b>Parameters</b>	<b>Requirements</b>	<b>Compliance Yes / No</b>
a.	License	Product to be manufactured as per IS : 14561:2014 or UL72 Class 350 for 2 Hr Rating	
b.	No. of years required in FRRC manufacturing Business	Minimum 10 years	
c.	FRFC Manufacturing Capacity	The company should have manufactured not less than 1000 FRFCs in the past three years, i.e. from the year 2014-15 to 201617. Copies of the form 3CA & form 3CD giving quantitative details of FRFCs manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document.	
d.	Order Execution	Tenderer should have received and supplied at least one single order of 10 Qty from any PSU Bank/ RRB. _	



### Specific Eligibility Criteria for Safe Deposit Locker Cabinet

Sr. No	Parameters	Requirements	Compliance Yes / No
a.	License	Product to be manufactured as per IS : 5244 :2014	
b.	No. of years required in SDL manufacturing Business	Minimum 10 years	
c.	SDL Manufacturing Capacity	The company should have manufactured not less than 1000 SDLs in the past three years, i.e. from the year 2014-15 to 201617. Copies of the form 3CA & form 3CD giving quantitative details of SDLs manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document.	
d.	Order Execution	Tenderer should have received and supplied atleast one single order of 10 Qty from any PSU Bank/ RRB.	

### Specific Eligibility Criteria for Safe with Safe Deposit Locker

Sr. No	Parameters	Requirements	Compliance Yes / No
a.	License	Product to be manufactured as per IS : 550:2014	
b.	No. of years required in SSDL manufacturing Business	Minimum 10 years	
c.	SSDL Manufacturing Capacity	The company should have manufactured not less than 1000 SSDLs in the past three years, i.e. from the year 2014-15 to 201617. Copies of the form 3CA & form 3CD giving quantitative details of SSDLs manufactured and certified by a registered tax auditor under section 44AB of Income Tax Act 1961 and Income Tax Rule 6G(2) should be attached as proof document.	
d.	Order Execution	Tenderer should have received and supplied atleast one single order of 10 Qty from any PSU Bank / RRB.	



## 1. Technical Specification for Class B Strong Room Door & Ventilator

### A. Main Door

The main door should be in accordance with IS 11188: 2014 (Part I) for general specification in addition to the following:

S. No.	Requirements	Compliance Yes / No
1.	The main door shall consist of outer and inner mild steel plates conforming to IS 2062:1992 for plates up to 15 mm thick strongly rimmed and continuously welded to form a single structure and tightly enclosing a monolithic one piece solid slab of high speed drill resisting and oxy acetylene torch resisting material that is at least 50 mm thick.	
2.	Door Frame : The doorframe should be one piece with a minimum thickness of 10 mm.	
3.	Thickness in door over locks: Should be of minimum 100 mm thickness.	
4.	Locks: The door should have a minimum of 2 high precision 8 lever dual control locks.	
5.	Protection to lock and relocker: Should be minimum 10 mm thick above the other barriers.	
6.	Lock Case: Should be minimum 2 step case construction covering entire jamb area.	
7.	Bolt Work: The bolt work should be mounted on a secure base transmitting motion to shooting bolts on both the sides.	
8.	The door should have been tested for fire endurance for a minimum of 30 minutes at least.	
9.	Automatic relocking device should be fitted on the door which comes into operation if the lock is dislodged with explosives or other means.	
10.	Grill Gate : is to be hinged such that it opens inside and an unpickable dual control lock capable of operating from both sides is to be provided.	

### B. Air-ventilator

S. No.	Requirements	Compliance Yes / No
1.	Air Ventilator is a box shaped steel unit or structure (channel). It provides a free passage for the air flow. For facilitating perfect gripping of the strong room wall, this ventilator is adjusted to the required thickness with in the specified limit of 300 mm to 450 mm. The air ventilator is fitted with outer and inner barrier slab varying in thickness as per Chest Class . The entire structure is then welded to provide utmost security against burglary. Perforations are provided on the steel plates for the proper flow of air. Inside the ventilator structure, pair of baffle plates are provided (Inside the channel the ventilator is provided with a pair of baffle plates), which does not provide a direct passage for the airflow as well as flames from the fire caught outside the vault room. Beside this it also enhances the security of the ventilator.	



## 2. Tender Specifications - Class BB safe

S. No.	Requirements	Compliance Yes / No
1.	The safe dimensions and specification shall be as per IS 550 : 2014	
2.	The safe shall be marked with IS 550 listing mark as per BIS Rules.	
3.	The manufacturers at any given point should be in a position to produce the latest BIS certificate for the safe offered and quoted.	
4.	The safe must be tested at BIS accredited test house for acquiring BIS listing mark and not at any other test house or at manufacturer's premises.	
5.	On demand manufacturer shall submit BIS accredited test house testing report or a letter from BIS office to authenticate testing.	
6.	All the surfaces of the safe before painting shall be thoroughly degreased and cleaned of rust and scale preferably by sand blasting or by normal pickling process and treated chemically to prevent from rusting.	
7.	The safe shall be painted inside and outside with an Anti-corrosive primer followed by two undercoats of paints and finally painted with quick drying paint.	
8.	The outer and inner body of the safe should be made of Mild steel conforming to IS 2062:2008 and the total thickness shall be minimum 7 mm thick out of which the outer body plate should be of max 2.5 mm thick and more steel shall be on inner layer.	
9.	The thickness of door over the Bolt work should be minimum 92 mm.	
10.	Lock should be secured with oxy-acetylene torch protection plate with Automatic relocking device.	
11.	The thickness of the Torch and Tool resistant material in the body of the safe as well as in the door shall be minimum 72 mm.	





### 3. Technical Specification of Fire Resistant Record Cabinet

#### Construction of Fire Resistant Record Cabinet :

S. No.	Parameters	Requirements	Compliance Yes / No
1.	Design	<p>The cabinet shall be designed to protect the contents (paper media documents) against fire as well fall &amp; impact during fire. The Fire protection shall be for minimum 2 Hr rating as per IS: 14203 or UL 72 – Class 350.</p> <p>The external shell of the cabinet shall be 2 mm thick and internal shell 1.6 mm thick as per IS: 513, further fortified by suitable fire resistant barriers to meet the required protection. The overall protection to the contents shall be minimum 70 mm on all six sides.</p>	
2.	Door	The external door of the cabinet shall be minimum 2 mm thick as per IS: 513, further fortified with hard plate for min burglary protection and fire resistant barrier material to meet required fire protection.	
3.	Bolt work	The door shall be secured by four way locking mechanism / Bolt work with minimum 8 moving shooting bolts of minimum 20 mm diameter, shall be provided.	
4.	Locking	Minimum eight lever dual control key locks, made up of Brass (body and levers), as per IS: 729, & IS: 410, shall be provided.	
5.	Corrosion resistance process	All steel parts of the safe shall be processed for corrosion resistance, by seven-tank treatment and further primed with epoxy primer. The finishing layer shall be of best quality Nitro Cellulose paint.	
6.	Capacity and storage system	<p>The storage capacity shall be minimum as per BIS</p> <p>The cabinet shall be provided with minimum four nos. adjustable shelves.</p>	

#### Testing :

The FRRC should be tested at CBRI as per IS 14203 for Fire Endurance Test for 120 minutes. Certification for the same must be provided.



#### **4.Tender Specification - Fire Resisting Filing Cabinet**

The Fire Resisting Filing Cabinet dimensions and specification shall be as per IS 14561: 2014.

##### **Construction of the FRFC**

The Fire Resisting Filing Cabinet shall be of double walled type and manufactured in multibend construction with following features.

<b>S. No.</b>	<b>Requirements</b>	<b>Compliance Yes / No</b>
1.	The outer body should be of minimum 1mm thickness	
2.	The inner body should be of minimum 1mm thickness.	
3.	The thickness of the fire resisting material on all 5 sides should be minimum 55mm.	
4.	The drawer should be a independent 5 sided enclosure which isolates them from each other.	
5.	The overall thickness of the drawer should be minimum 75mm.	
6.	The drawer should be suspended on ball bearings.	
7.	The FRFC should have a tongue and groove construction that will divert hot gases from directly entering in to the cabinet.	
8.	The FRFC should have isolation catch that will allow it to be operational even is the top drawer is locked.	
9.	The FRFC should be provided with a 6 lever dual control lock on the top drawer.	
10.	The locking mechanism should be such that when the top drawer is pushed in fully, it actuates locking mechanism to lock all other drawers simultaneously.	
11.	The FRFC shall be painted with Polyurethane paint.	

##### **Testing :**

1. The Fire Resisting Filing Cabinet should be tested BIS labelled for Fire endurance for 120 minutes. Certification for the same must be provided.
2. The Fire Resisting Filing Cabinet should be tested at Underwriter Laboratory as per UL 72 for Fire endurance for 120 minutes. Certification for the same must be provided.
3. The Fire Resisting Filing Cabinet should be tested at Underwriter Laboratory as per UL 72 for Fire and Impact. Certification for the same must be provided.
4. The Fire Resisting Filing Cabinet should be tested at Underwriter Laboratory as per UL 72 for Explosion Hazard. Certification for the same must be provided. \_



### **5 .Technical Specifications for Safe with Safe Deposit Lockers**

S. No.	Requirements	Compliance Yes / No
1.	The Design of the Safe cum Safe Deposit locker( SSDL) should be conforming to IS 550:2014.	
2.	The SSDL shall be made in accordance with details laid down as per BIS	
3.	The Safe cum Safe Deposit lockers shall be made in accordance with details laid down in IS 5244 standards.	
4.	All the surfaces of the SSDL before painting shall be thoroughly degreased and cleaned of rust and scale preferably by sand blasting or by normal pickling process and treated chemically to prevent from rusting.	
5.	The SSDL shall be painted inside and outside with an Anti-corrosive primer followed by two undercoats of paints and finally painted with quick drying paint.	
6.	The outer and inner body of the SSDL should be made of Mild steel conforming to IS 2062:2008 and the total thickness shall be minimum 7 mm thick out of which the outer body plate should be 5 mm thick.	
7.	The SSDL should have a two step lock case construction and in the closed position the gap at any place between the door edge and the frame shall not exceed 1 mm and in locked position it shall not have a play of more than 1 mm in the direction in which the door opens.	
8.	The thickness of door over the Bolt work should be 83 mm min.	
9.	Depth of the Barrier material in the body should be 90 mm and door 60 mm.	
10.	Lock should be provided with Drill Deflecting shield with Automatic relocking device.	
11.	The SSDL should have passed the 60 minutes Fire Endurance test as per UL 72 Class 350 and suitable test certificate should be attached for the same.	
12.	Manufacturers providing the safe with TL 30 rating as per UL 687 shall be preferred.	
13.	The SSDL should be such that the boltwork ( bolts) should be movable on both sides. No passive inactive bolts will be used.	

### **6. Tender Specifications for Safe Deposit Locker Cabinet**

S. No.	Requirements	Compliance Yes / No
1.	The cabinet dimensions and specification shall be as per IS 5244:2014	
2.	All other sides of the lockers should be made of 5 mm high grade steel.	
3.	The front or door plate of the shelves shall be reinforced of 10 mm high grade steel.	
4.	The shelves and partitions shall be made of 2mm thick steel.	
5.	It shall be fitted with a high precision, unpickable, dual control 7 lever lock.	
6.	All steel components shall be given anti rust treatment.	
7.	For enhanced security, the cabinets should have provision for fitment of renter personal lock and pad locking hasps.	



**Annexure - II**

**Financial Bid**

Sr. No.	Particulars of Equipment	BIS No.	Unit rate inclusive of all taxes & govt. duties and installation and delivery charges at the location. ( in ₹ )
1.	Strong room door + Grill gate with clenching mechanism class 'B' TRTL 30	IS 11188:2014	
2.	Strong room door w/o Grill gate class 'B' TRTL 30	IS 11188:2014	
3.	Air-Ventilator		
4.	Exhaust Fan		
5.	V-Cage		
6.	61" Cash Safe Class 'BB' TRTL 15 x 6	IS 550:2014	
7.	49" Cash Safe Class 'BB' TRTL 15 x 6	IS 550:2014	
8.	FRRC ( Fire Resistance Record Cabinet ) 2 Hours Rating	IS 14203:1999	
9.	FRFC ( Fire Resistance Filing Cabinet ) 4 Drawer, 2 Hours rating	IS 14561:2014	
10.	75 Safe Deposit Locker Cabinet ( 75 SDL)	IS 5244:2014	
11.	90 Safe Deposit Locker Cabinet (90 SDL)	IS 5244:2014	
12.	45 Safe Deposit Locker Cabinet (45 SDL)	IS 5244:2014	
13.	56 Safe with Safe Deposit Locker Cabinet ( 56 SSDL)	IS 550:2014	
14.	46 Safe with Safe Deposit Locker Cabinet ( 46 SSDL)	IS 550:2014	
15.	Buy back of old 49" Cash Safes irrespective of the manufacturers		
16.	Buy back of old 61" Cash Safes irrespective of the manufacturers		

Above rates are inclusive of all taxes & F.O.R. Destination. Rates should be quoted in word also, in case of any discrepancy in this regard the rates in word will be considered valid.

Date :

Signature, Name & Seal of Tendrer

